

# MATERIAL SAFETY DATA SHEET

## SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

As of the revision date above, this (M)SDS meets the regulations in New Zealand.

### PRODUCT

**Product Name:** ULTRA LOW SULPHUR DIESEL  
**Product Description:** Hydrocarbons and Additives  
**Product Code:** 152017  
**Intended Use:** Fuel

### COMPANY IDENTIFICATION

**Supplier:** Mobil Oil New Zealand Pty Ltd  
MOBIL ON THE PARK  
157 LAMBTON QUAY  
WELLINGTON New Zealand

**NATIONAL POISON CENTRE (24hr)** +64 3 479 7248/ Freephone 0800 764 766  
**Product Technical Information** 0800 732 275  
**Mobil Oil New Zealand Limited Contact (24hr)** +64-4-4984 000

## SECTION 2 HAZARDS IDENTIFICATION

Refer to Section 15 for HSNO classification.

**EU CLASSIFICATION:** | Carc. Cat. 3; R40 | Xn; R65 | R66 | N; R51/53 |

### PHYSICAL / CHEMICAL HAZARDS

Material can release vapours that readily form flammable mixtures. Vapour accumulation could flash and/or explode if ignited. Material can accumulate static charges which may cause an incendiary electrical discharge.

### HEALTH HAZARDS

Limited evidence of a carcinogenic effect. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking. Under conditions of poor personal hygiene and prolonged repeated contact, some polycyclic aromatic compounds (PACs) have been suspected as a cause of skin cancer in humans. May be irritating to the eyes, nose, throat, and lungs. High-pressure injection under skin may cause serious damage.

### ENVIRONMENTAL HAZARDS

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Note:** This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

## SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

This material is regulated as a preparation.

Product Name: ULTRA LOW SULPHUR DIESEL

Revision Date: 05Apr2006

Page 2 of 9

### Reportable Hazardous Substance(s) or Complex Substance(s)

Name	CAS#	Concentration*	Symbols/Risk Phrases
Fuels, diesel	68334-30-5	> 99 %	Xn;Carc. Cat. 3;R40, Xn;R65, R66, N;R51/53

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Note: Composition may contain up to 0.5% performance additives and / or dyes.

## SECTION 4 FIRST AID MEASURES

### INHALATION

Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

### SKIN CONTACT

Remove contaminated clothing. Dry wipe exposed skin and cleanse with waterless hand cleaner and follow by washing thoroughly with soap and water. For those providing assistance, avoid further skin contact to yourself or others. Wear impervious gloves. Launder contaminated clothing separately before reuse. Discard contaminated articles that cannot be laundered. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

### EYE CONTACT

Flush thoroughly with water. If irritation occurs, get medical assistance.

### INGESTION

Seek immediate medical attention. Do not induce vomiting.

### NOTE TO PHYSICIAN

If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

### PRE-EXISTING MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED BY EXPOSURE

Hydrocarbon Solvents/Petroleum Hydrocarbons- Skin contact may aggravate an existing dermatitis.

## SECTION 5 FIRE FIGHTING MEASURES

### EXTINGUISHING MEDIA

**Appropriate Extinguishing Media:** Use water fog, foam, dry chemical or carbon dioxide (CO<sub>2</sub>) to extinguish flames.

**Inappropriate Extinguishing Media:** Straight streams of water

### FIRE FIGHTING

**Fire Fighting Instructions:** Evacuate area. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. Fire-fighters should use standard protective equipment and in

Product Name: ULTRA LOW SULPHUR DIESEL

Revision Date: 05Apr2006

Page 3 of 9

enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

**Hazardous Combustion Products:** Aldehydes, Oxides of carbon, Sulphur Oxides, Incomplete combustion products, Smoke, Fume

#### FLAMMABILITY PROPERTIES

**Flash Point [Method]:** 64C (147F) [ASTM D-93]

**Flammable Limits (Approximate volume % in air):** LEL: 0.6 UEL: 7.0

**Autoignition Temperature:** N/D

### SECTION 6 ACCIDENTAL RELEASE MEASURES

#### NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

#### PROTECTIVE MEASURES

Avoid contact with spilled material. Warn or evacuate occupants in surrounding and downwind areas if required, due to toxicity or flammability of the material. See Section 5 for fire fighting information. See Section 3 for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for Personal Protective Equipment.

#### SPILL MANAGEMENT

**Land Spill:** Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Prevent entry into waterways, sewer, basements or confined areas. A vapour-suppressing foam may be used to reduce vapour. Use clean non-sparking tools to collect absorbed material. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Large Spills: Water spray may reduce vapour, but may not prevent ignition in enclosed spaces.

**Water Spill:** Stop leak if you can do so without risk. Warn other shipping. Seek the advice of a specialist before using dispersants. Eliminate sources of ignition. If the Flash Point does not exceed the Ambient Temperature by 10 deg C or is less than the Ambient Temperature, use booms as a barrier to protect shorelines and allow the material to evaporate. If the Flash Point exceeds the Ambient Temperature by 10 deg C or more, use containment booms and remove from the surface by skimming or with suitable absorbents when conditions permit.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

#### ENVIRONMENTAL PRECAUTIONS

Large Spills: Dyke far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

### SECTION 7 HANDLING AND STORAGE

#### HANDLING

Avoid contact with skin. Do not siphon by mouth. Use proper bonding and/or earthing procedures. Do not use

Product Name: ULTRA LOW SULPHUR DIESEL

Revision Date: 05Apr2006

Page 4 of 9

as a cleaning solvent or other non-motor fuel uses. For use as a motor fuel only. Do not use electronic devices (including but not limited to cellular phones, computers, calculators, pagers or other electronic devices etc) in or around any fuelling operation or storage area unless the devices are certified intrinsically safe by an approved national testing agency and to the safety standards required by national and/or local laws and regulations. Prevent small spills and leakage to avoid slip hazard.

**Static Accumulator:** This material is a static accumulator.

## STORAGE

Keep container closed. Handle containers with care. Open slowly in order to control possible pressure release. Store in a cool, well-ventilated area. Storage containers should be earthed and bonded. Drums must be earthed and bonded and equipped with self-closing valves, pressure vacuum bungs and flame arresters.

## SECTION 8

## EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE LIMIT VALUES

**Exposure limits/standards (Note: Exposure limits are not additive)**

Substance Name	Form	Limit/Standard		Note	Source	Year
FUELS, DIESEL [total hydrocarb, vapour&aerosol]	Vapour and aerosol.	TWA	100 mg/m3	Skin	ACGIH	2005
Total Hydrocarbons	Stable Aerosol.	TWA	5 mg/m3		ExxonMobil	2005
Total Hydrocarbons	Total vapour and aerosol.	TWA	500 mg/m3	100 ppm	ExxonMobil	2005

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

### ENGINEERING CONTROLS

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:

Use explosion-proof ventilation equipment to stay below exposure limits.

### PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

**Respiratory Protection:** If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:

No special requirements under ordinary conditions of use and with adequate ventilation. Organic vapour

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode.

Product Name: ULTRA LOW SULPHUR DIESEL

Revision Date: 05Apr2006

Page 5 of 9

Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapour warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

**Hand Protection:** Any specific glove information provided is based on published literature and glove manufacturer data. Work conditions can greatly effect glove durability; inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

If prolonged or repeated contact is likely, chemical-resistant gloves are recommended. If contact with forearm is likely, wear gauntlet-style gloves. Viton, Nitrile

**Eye Protection:**

**Skin and Body Protection:** Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include:

If prolonged or repeated contact is likely, chemical, and oil resistant clothing is recommended.

**Specific Hygiene Measures:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

## ENVIRONMENTAL CONTROLS

See Sections 6, 7, 12, 13.

## SECTION 9

## PHYSICAL AND CHEMICAL PROPERTIES

Typical physical and chemical properties are given below. Consult the Supplier in Section 1 for additional data.

### GENERAL INFORMATION

**Physical State:** Liquid  
**Colour:** Clear (May Be Dyed)  
**Odour:** petroleum/solvent  
**Odour Threshold:** N/D

### IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION

**Relative Density (at 15 C):** 0.84  
**Flash Point [Method]:** 64C (147F) [ASTM D-93]  
**Flammable Limits (Approximate volume % in air):** LEL: 0.6 UEL: 7.0  
**Autoignition Temperature:** N/D  
**Boiling Point / Range:** 185C (365F)  
**Vapour Density (Air = 1):** > 2 at 101 kPa  
**Vapour Pressure:** 0.067 kPa (0.5 mm Hg) at 20 C  
**Evaporation Rate (N-Butyl Acetate = 1):** N/D  
**pH:** N/A  
**Log Pow (n-Octanol/Water Partition Coefficient):** > 3.5  
**Solubility in Water:** Negligible  
**Viscosity:** 2.7 cSt (2.7 mm<sup>2</sup>/sec) at 40 C  
**Oxidising properties:** See Sections 3, 15, 16.

### OTHER INFORMATION

Product Name: ULTRA LOW SULPHUR DIESEL

Revision Date: 05Apr2006

Page 6 of 9

**Freezing Point:** N/D  
**Melting Point:** N/A  
**Pour Point:** -18°C (-1°F)

<b>SECTION 10</b>	<b>STABILITY AND REACTIVITY</b>
-------------------	---------------------------------

**STABILITY:** Material is stable under normal conditions.

**CONDITIONS TO AVOID:** Open flames and high energy ignition sources. High energy sources of ignition.

**MATERIALS TO AVOID:** Halogens, Alkalies, Strong Acids, Strong oxidisers

**HAZARDOUS DECOMPOSITION PRODUCTS:** Material does not decompose at ambient temperatures.

**HAZARDOUS POLYMERIZATION:** Will not occur.

<b>SECTION 11</b>	<b>TOXICOLOGICAL INFORMATION</b>
-------------------	----------------------------------

**Acute Toxicity**

<u>Route of Exposure</u>	<u>Conclusion / Remarks</u>
<b>INHALATION</b>	
Toxicity (Rat): LC50 > 5000 mg/m <sup>3</sup>	Minimally Toxic. Based on test data for structurally similar materials.
Irritation: Data available.	Elevated temperatures or mechanical action may form vapours, mist, or fumes which may be irritating to the eyes, nose, throat, or lungs. Based on test data for structurally similar materials.
<b>INGESTION</b>	
Toxicity (Rat): LD50 > 2000 mg/kg	Minimally Toxic. Based on test data for structurally similar materials.
<b>Skin</b>	
Toxicity (Rabbit): LD50 > 2000 mg/kg	Minimally Toxic. Based on test data for structurally similar materials.
Irritation: Data available.	May dry the skin leading to discomfort and dermatitis. Based on test data for structurally similar materials.
<b>Eye</b>	
Irritation: Data available.	May cause mild, short-lasting discomfort to eyes. Based on test data for structurally similar materials.

**CHRONIC/OTHER EFFECTS**

**For the product itself:**

Vapour concentrations above recommended exposure levels are irritating to the eyes and the respiratory tract, may cause headaches and dizziness, are anaesthetic and may have other central nervous system effects. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema.

Diesel fuel: Carcinogenic in animal tests. Caused mutations in-vitro. Repeated dermal exposures to high concentrations in test animals resulted in reduced litter size and litter weight, and increased fetal resorptions at maternally toxic doses. Dermal exposure to high concentrations resulted in severe skin irritation with weight loss and some mortality. Inhalation exposure to high concentrations resulted in respiratory tract irritation, lung changes/infiltration/accumulation, and reduction in lung function. Diesel exhaust fumes: Carcinogenic in

Product Name: ULTRA LOW SULPHUR DIESEL

Revision Date: 05Apr2006

Page 7 of 9

---

animal tests. Inhalation exposures to exhaust for 2 years in test animals resulted in lung tumours and lymphoma. Extract of particulate produced skin tumours in test animals. Caused mutations in-vitro.

Additional information is available by request.

**IARC Classification:**

**The Following Ingredients are Cited on the Lists Below:** None.

--REGULATORY LISTS SEARCHED--

1 = IARC 1

2 = IARC 2A

3 = IARC 2B

<b>SECTION 12</b>
-------------------

<b>ECOLOGICAL INFORMATION</b>
-------------------------------

The information given is based on data available for the material, the components of the material, and similar materials.

**ECOTOXICITY**

Material -- Expected to be toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

**MOBILITY**

More volatile component -- Highly volatile, will partition rapidly to air. Not expected to partition to sediment and wastewater solids.

High molecular wt. component -- Low solubility and floats and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.

**PERSISTENCE AND DEGRADABILITY**

**Biodegradation:**

Majority of components -- Expected to be inherently biodegradable

**Atmospheric Oxidation:**

More volatile component -- Expected to degrade rapidly in air

**BIOACCUMULATION POTENTIAL**

Base oil component -- Has the potential to bioaccumulate, however metabolism or physical properties may reduce the bioconcentration or limit bioavailability.

<b>SECTION 13</b>
-------------------

<b>DISPOSAL CONSIDERATIONS</b>
--------------------------------

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

**DISPOSAL RECOMMENDATIONS**

Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products.

Product Name: ULTRA LOW SULPHUR DIESEL

Revision Date: 05Apr2006

Page 8 of 9

**Empty Container Warning** (where applicable): Empty containers may retain residue and can be dangerous. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Do not attempt to refill or clean container since residue is difficult to remove. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

## SECTION 14

## TRANSPORT INFORMATION

**LAND** : Not Regulated for Land Transport

**SEA (IMDG)** : Not Regulated for Sea Transport according to IMDG-Code

**AIR (IATA)** : Not Regulated for Air Transport

## SECTION 15

## REGULATORY INFORMATION

**Material is dangerous as defined by the EU Dangerous Substances/Preparations Directives.**

**CLASSIFICATION:** Category 3 Carcinogen. Harmful. Dangerous for the environment.

### EU LABELING:

**Symbol:** Xn, N



Harmful.



Dangerous for the environment.

**Nature of Special Risk:** R40; Limited evidence of a carcinogenic effect. R65; Harmful: may cause lung damage if swallowed. R66; Repeated exposure may cause skin dryness or cracking. R51/53; Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Safety Advice:** S2; Keep out of the reach of children. S24; Avoid contact with skin. S36/37; Wear suitable protective clothing and gloves. S51; Use only in well-ventilated areas. S61; Avoid release to the environment. Refer to special instructions/safety data sheets. S62; If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

**Contains:** GAS OIL - UNSPECIFIED

## REGULATORY STATUS AND APPLICABLE LAWS AND REGULATIONS

**This material has been classified according to the Environmental Risk Management Authority (ERMA)**

Product Name: ULTRA LOW SULPHUR DIESEL  
Revision Date: 05Apr2006  
Page 9 of 9

---

**under ERMA Approval Code:** HSR001441

**HSNO Hazard Classification:**

- 3.1D - Flammable liquids: low hazard
- 6.1E - Acutely toxic
- 6.3B - Mildly irritating to the skin.
- 6.7B - Suspected human carcinogens.
- 9.1B - Ecotoxic in the aquatic environment.

**Complies with the following national/regional chemical inventory requirements:** AICS, EINECS, PICCS, TSCA

<b>SECTION 16</b>	<b>OTHER INFORMATION</b>
-------------------	--------------------------

**N/D = Not determined, N/A = Not applicable**

**KEY TO THE RISK CODES CONTAINED IN SECTION 2 AND 3 OF THIS DOCUMENT (for information only):**

- R40; Limited evidence of a carcinogenic effect.
- R51/53; Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65; Harmful: may cause lung damage if swallowed.
- R66; Repeated exposure may cause skin dryness or cracking.

**THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:**

No revision information is available.

---

The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest.

---

DGN: 7041200XNZ (1011103)

---

**\*\*End of (M)SDS\*\***